


GLAZED VITRIFIED TILES 600x1200 mm







REXTRON CERAMIC























Low Water Absorption


Frost Resistant

Chemical Stain Zero Resistant Resistance Maintenance

Easy to Clean



REXTRON CERAMIC























Low Water

Frost Resistant

Chemical Stain Zero Resistant Resistance Maintenance

Easy to



3D 2003



REXTRON CERAMIC





















Low Water Absorption

Frost Resistant

Chemical Stain Zero Resistant Resistance Maintenance


Easy to Clean



600x1200mm **GLAZED VITRIFIED TILES**

REXTRON CERAMIC

















Low Water Frost Absorption Resistant

Resistant Resistance Maintenance





3D 2005



REXTRON CERAMIC





















ow Water

st Ch

Stain Zero Resistance Maintenance

Easy to Clean



REXTRON CERAMIC

















Low Water Absorption

Frost Resistant

al Stain Zero nt Resistance Maintenance


Easy to Clean






REXTRON CERAMIC

6 0 0 x 1 2 0 0 m m

















Low Water Absorption

Frost Resistant

Stain Zero Resistance Maintenance


Easy to Clean






REXTRON CERAMIC

600x1200mm **GLAZED VITRIFIED TILES**


















Low Water Frost Absorption Resistant

Resistant Resistance Maintenance





REXTRON CERAMIC















Low Water

rost (istant F


Stain Zero Resistance Maintenance


Easy to Clean



RON CERAMIC

600x1200mm **GLAZED VITRIFIED TILES**


















Low Water Frost Absorption Resistant


Resistant Resistance Maintenance



600x1200mm **GLAZED VITRIFIED TILES**

ZEXTRON CERAMIC

















Low Water Frost Absorption Resistant

Resistant Resistance Maintenance





3D 2012



REXTRON CERAMIC





















Low Water Absorption

Frost Resistant


Chemical Stain Zero Resistant Resistance Maintenance


Easy to Clean



REXTRON CERAMIC

600x1200mm **GLAZED VITRIFIED TILES**

















Low Water Frost Absorption Resistant


Resistant Resistance Maintenance






600x1200mm **GLAZED VITRIFIED TILES**

REXTRON CERAMIC

















Low Water Frost Absorption Resistant

Resistant Resistance Maintenance






6 0 0 x 1 2 0 0 m m

REXTRON CERAMIC

3D 2015











Resistant







Low Water Absorption

Frost Resistant


Stain Zero Resistance Maintenance


Easy to Clean





REXTRON CERAMIC

















Low Water Absorption

Frost esistant

Stain Zero Resistance Maintenance


Easy to Clean





REXTRON CERAMIC

















Low Water Absorption

Frost Resistant

ical Stain Zero ant Resistance Maintenance

Easy to Clean



REXTRON CERAMIC

















Low Water Absorption

rost istant


Stain Zero Resistance Maintenance

Easy to Clean



REXTRON CERAMIC





















Low Water Absorption

Frost (

Stain Zero Resistance Maintenance


Easy to Clean



REXTRON CERAMIC

6 0 0 x 1 2 0 0 m m GLAZED VITRIFIED TILES

3D 2020


















Low Water Absorption Frost Resistant


Chemical Stain Zero Resistant Resistance Maintenance

Easy to



REXTRON CERAMIC

















Low Water Absorption

Frost C

Stain Zero Resistance Maintenance


Easy to Clean





REXTRON (R)

















Low Water

Frost Resistant

Chemical Stain Zero Resistant Resistance Maintenance

Easy to Clean





PACKING DETAIL FOR 600x1200MM GVT TILES							
Nominal Size	Thickness(mm)	Average weight per carton (Kgs)	No. of tiles per carton	Coverage area per carton			
600x1200mm	8.5 (Approx)	27.50 (Approx)	2	1.44sq.mtr./15.50sq.ft.			

TECHNICAL SPECIFICATION FOR 600x1200MM GVT TILES							
Characteristics	Requirement as per IS 15622 : 2017 < E ≤ 0.08 Group Bla	Requirement as per ISO 13006 ≤ 0.5% Group Bla	Our Values	Test Method			
A) Dimension & Surface Quality							
I) Length & Width	± 0.1%	± 0.3%	± 0.1%	IS 13630 Part 1/ ISO 10545-2			
ii) Thickness	± 5.0%	± 5.0%	± 4.0%				
iii) Straightness of Side	± 0.1%	± 0.3%	± 0.1%				
iv) Rectengularity	± 0.1%	± 0.3%	± 0.1%				
v) Surface Flatness							
a) Center curvature (%) (max.Deviation)	± 0.5%	± 0.4%	± 0.2 %				
b) Edge curvature (%) { max.Deviation)	± 0.5%	± 0.4%	± 0.2 %				
c) Corner warpage (%)(max.Deviation)	± 0.5%	± 0.4%	± 0.2 %				
vi) Surface Quality	Min. 95 % of tiles will be free from visible defects	Min. 95 % of tiles will be free from visible defects	Min. 95 % of tiles will be free from visible defects				
B) Physical Properties							
I) Water Absorption	Av E ≤ 0.08 %, Individual 0.1 max	Av ≤ 0.5 %, Individual 0.6% max	Avg. E≤ 0.08 %	IS 13630 Part 2/ ISO 10545-3			
ii) Modulus of Rupture [N/mm2]	Av 35, Individual 32 min	Av 35, Individual 32 min	Avg, 35 Ind 32	IS 13630 Part 6/ISO 10545-4			
iii) Breaking Strength in N	Min. 1300	Min. 1300	Min. 1300	10 13030 Falt 0/100 10345-4			
iv) Moisture Expansion in mm/m	0.02	Test Method Available	0.02	IS 13630 Part 3/ISO-10545-10			
v) Scratch Hardness of surface (Mohs)	Min 5	N/A	Min.5 (for VC & RT), Min.3 (for Polished)	IS 13630 Part 13			
vi) Resistance to Abrasion of glazed tiles(Class I to V)	Min II	Abrasion Class & Cycle passed	Class-V (for VC & RT), Class-III (for Polished)	IS 13630 Part 11 /ISO 10545-7			
vii) Coefficient of linear thermal expansion from embiant temperature to 100° C	6 X 10 ⁻⁶ K ⁻¹ Max	Test Method Available	Max 6 X 10 ⁻⁶ K ⁻¹ max	IS 13630 Part 4/ ISO 10545-8			
viii) Thermal Shock Resistance	10 cycle min	Test Method Available	10 cycle passed	IS 13630 Part 5/ISO-10545-9			
ix) Crazing Resistance	4 cycle @ 7.5bar min	Required	4 cycle passed	IS 13630 Part 9/ISO 10545-11			
x) Impact Resistance as Co-efficient of Re stitution	0.55 min	Required	Min 0.55	ISO 10545-5			
xi) Frost Resistance	Required	Required	100 Cycle Passed	IS 13630 Part 10/ISO 10545-12			
C) Chemical Resistance (glazed Tiles)							
l) Stain Resistance	Min Class 1	Min Class 3	Min Class-1	IS 13630 Part 8 &ISO 10545-14			
ii) Resistance to household chemicals	Min Class AA	Min Class GB	Min Class AA	IS 13630 Part 8/ ISO 10545-13			
iii) Resistance to acids and alkalis (with exception of hydrofluoric acid and its compounds)	Required if agreed	Declared Value	Min Class AA				

The reproduction of tiles in this catalogue is restricted to four color printing only and tiles are not in relative sizes, therefore customers are advised to see the physical sample before placing the order. "Technical Specification" for Arkstone wall & floor tiles are applicable only for premium quality tiles. Please inspect all tiles prior to installation. Company will not entertain complaints once tiles are laid/fixed.

Complaints will not be entertained for Borders, Highlighters & Motifs.